# SIGMA-ALDRICH

# **Material Safety Data Sheet**

Version 5.1 Revision Date 10/01/2012 Print Date 03/19/2013

| 1. PRODUCT AND COMPANY IDENTIFICATION                        |   |   |  |  |  |
|--|---|---|--|--|--|
| Product name   | : | 2-Mercaptoethanol   |  |  |  |
| Product Number<br>Brand                                      | : | M6250<br>Aldrich  |  |  |  |
| Supplier   | : | Sigma-Aldrich<br>3050 Spruce Street<br>SAINT LOUIS MO 63103<br>USA              |  |  |  |
| Telephone  |   | +1 800-325-5832   |  |  |  |
| Fax  | : | +1 800-325-5052   |  |  |  |
| Emergency Phone # (For<br>both supplier and<br>manufacturer) | : | (314) 776-6555  |  |  |  |
| Preparation Information                                      | : | Sigma-Aldrich Corporation<br>Product Safety - Americas Region<br>1-800-521-8956 |  |  |  |

# 2. HAZARDS IDENTIFICATION

#### **Emergency Overview**

#### **OSHA Hazards**

Toxic by inhalation., Toxic by ingestion, Highly toxic by skin absorption, Skin sensitiser, Corrosive, Mutagen

Other hazards which do not result in classification Stench., Rapidly absorbed through skin.

#### **GHS Classification**

Flammable liquids (Category 4) Acute toxicity, Oral (Category 3) Acute toxicity, Inhalation (Category 3) Acute toxicity, Dermal (Category 2) Skin irritation (Category 2) Serious eye damage (Category 1) Skin sensitization (Category 1) Specific target organ toxicity - repeated exposure, Oral (Category 2), Liver, Heart Acute aquatic toxicity (Category 1) Chronic aquatic toxicity (Category 1)

# GHS Label elements, including precautionary statements

Pictogram



Signal word

|                     | -  |
|---------------------|--|
| Hazard statement(s) |  |
| H227                | Combustible liquid   |
| H301 + H331         | Toxic if swallowed or if inhaled   |
| H310                | Fatal in contact with skin.  |
| H315                | Causes skin irritation.  |
| H317                | May cause an allergic skin reaction.   |
| H318                | Causes serious eye damage.   |
| H373                | May cause damage to organs (Liver, Heart) through prolonged or repeated exposure if swallowed. |
|                     |  |

| H410  | Very toxic to aquatic life with long lasting effects.  |
|---|--|
| -   |  |
| Precautionary statement(s)<br>P261<br>P273<br>P280<br>P302 + P350<br>P305 + P351 + P338<br>P310       | Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.<br>Avoid release to the environment.<br>Wear protective gloves/ eye protection/ face protection.<br>IF ON SKIN: Gently wash with plenty of soap and water.<br>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if<br>present and easy to do. Continue rinsing.<br>Immediately call a POISON CENTER or doctor/ physician. |
| P501  | Dispose of contents/ container to an approved waste disposal plant.  |
| Other hazards<br>Stench.  |  |
| HMIS Classification<br>Health hazard:<br>Chronic Health Hazard:<br>Flammability:<br>Physical hazards: | 3<br>*<br>0<br>0   |
| NFPA Rating<br>Health hazard:<br>Fire:<br>Reactivity Hazard:  | 3<br>0<br>0  |
| Potential Health Effects  |  |
| Inhalation  | Toxic if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract.   |
| Skin<br>Eyes<br>Ingestion   | May be fatal if absorbed through skin. Causes skin burns.<br>Causes eye burns.<br>Toxic if swallowed.  |
| 3. COMPOSITION/INFORMATION  | ON INGREDIENTS   |
| Synonyms  | : Thioethylene glycol<br>2-Hydroxyethylmercaptan<br>BME<br>β-Mercaptoethanol   |

| Formula           | : C <sub>2</sub> H <sub>6</sub> OS |               |
|-------------------|------------------------------------|---------------|
| Molecular Weight  | : 78.13 g/mol                      |               |
| Component         |                                    | Concentration |
| 2-Mercaptoethanol |                                    |               |
| CAS-No.           | 60-24-2                            | -             |
| EC-No.            | 200-464-6                          |               |
|                   |                                    |               |

# **4. FIRST AID MEASURES**

# General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

#### In case of eye contact

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.Continue rinsing eyes during transport to hospital.

# If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### **5. FIREFIGHTING MEASURES**

#### Conditions of flammability

Not flammable or combustible.

#### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

#### Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

#### Hazardous combustion products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sulphur oxides

#### Further information

Use water spray to cool unopened containers.

# 6. ACCIDENTAL RELEASE MEASURES

#### **Personal precautions**

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

#### **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

#### Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Recommended storage temperature: 2 - 8 °C

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# Components with workplace control parameters

| Components            | CAS-No. | Value | Control<br>parameters | Basis  |
|-----------------------|---------|-------|-----------------------|--|
| 2-<br>Mercaptoethanol | 60-24-2 | TWA   | 0.2 ppm               | USA. Workplace Environmental Exposure Levels<br>(WEEL) |
| Remarks               | Skin    |       |                       |  |

#### Personal protective equipment

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Hand protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Immersion protection Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: > 480 min Material tested:Butoject® (Aldrich Z677647, Size M)

Splash protection Material: Nature latex/chloroprene Minimum layer thickness: 0.6 mm Break through time: > 30 min Material tested:Lapren® (Aldrich Z677558, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 873000, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### Eye protection

Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin and body protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

# **Hygiene measures**

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

# Appearance

| Form                            | liquid  |
|---------------------------------|---|
| Colour                          | colourless<br>yellow  |
| Safety data                     |   |
| рН                              | 4.5 - 6 at 500 g/l at 20 °C (68 °F)   |
| Melting<br>point/freezing point | < -50 °C (< -58 °F)   |
| Boiling point                   | 157 °C (315 °F) - lit.  |
| Flash point                     | no data available   |
| Ignition temperature            | 295 °C (563 °F) at 1,013 hPa (760 mmHg)   |
| Autoignition<br>temperature     | no data available   |
| Lower explosion limit           | 2.3 %(V)  |
| Upper explosion limit           | 18 %(V)   |
| Vapour pressure                 | 0.76 hPa (0.57 mmHg) at 20 °C (68 °F)<br>4.67 hPa (3.50 mmHg) at 40 °C (104 °F) |
| Density                         | 1.114 g/cm3 at 25 °C (77 °F)  |
| Water solubility                | soluble   |
| Partition coefficient:          | log Pow: -0.326   |

n-octanol/water log Pow: -0.056 at 25 °C (77 °F) Relative vapour density - (Air = 1.0) Odour Odour Threshold no data available Evaporation rate no data available

# **10. STABILITY AND REACTIVITY**

#### **Chemical stability**

Stable under recommended storage conditions.

#### **Possibility of hazardous reactions** no data available

**Conditions to avoid** Heat, flames and sparks.

Materials to avoid Metals, Oxidizing agents

#### Hazardous decomposition products

Hazardous decomposition products formed under fire conditions. - Carbon oxides, Sulphur oxides Other decomposition products - no data available

# **11. TOXICOLOGICAL INFORMATION**

## Acute toxicity

Oral LD50 LD50 Oral - rat - 98 - 162 mg/kg

Inhalation LC50 LC50 Inhalation - rat - 4 h - 2 mg/l

LC50 Inhalation - rat - 4 h - 625 ppm

#### Dermal LD50

LD50 Dermal - rabbit - 112 - 224 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation Skin - rabbit - Irritating to skin. - Draize Test

# Serious eye damage/eye irritation

Eyes - rabbit - Risk of serious damage to eyes.

**Respiratory or skin sensitization** Maximisation Test - guinea pig - OECD Test Guideline 406 - May cause sensitization by skin contact.

#### Germ cell mutagenicity

Experiments showed mutagenic effects in cultured bacterial cells.

#### Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

no data available

Teratogenicity

no data available

#### Specific target organ toxicity - single exposure (Globally Harmonized System)

no data available

#### Specific target organ toxicity - repeated exposure (Globally Harmonized System)

Ingestion - May cause damage to organs through prolonged or repeated exposure. - Liver, Heart

# Aspiration hazard no data available

#### Potential health effects

| Inhalation | Toxic if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. |
|------------|--|
| Ingestion  | Toxic if swallowed.  |
| Skin       | May be fatal if absorbed through skin. Causes skin burns.  |
| Eyes       | Causes eye burns.  |

#### Signs and Symptoms of Exposure

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Weakness, Unconsciousness, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema

# Synergistic effects

no data available

# Additional Information

RTECS: KL5600000

# **12. ECOLOGICAL INFORMATION**

#### Toxicity

| Toxicity to fish  | LC50 - Leuciscus idus (Golden orfe) - 46 - 100 mg/l - 96.0 h          |
|---|---|
| Toxicity to daphnia<br>and other aquatic<br>invertebrates | EC50 - Daphnia - 1.52 mg/l - 48 h                                     |
|   | EC50 - Daphnia - 0.89 mg/l  - 48 h<br>Method: OECD Test Guideline 202 |
| Toxicity to algae   | EC50 - Desmodesmus subspicatus (green algae) - 12 mg/l - 72 h         |
| Toxicity to bacteria                                      | LC50 - Bacteria - 125 mg/l - 17 h                                     |
| Persistence and degrad<br>Biodegradability                | ability<br>Result: < 30.0 % - Not readily biodegradable.              |
|   | Result: 6 % - Not readily biodegradable.                              |
|   | aerobic<br>Result: < 10 % - Not readily biodegradable.                |

# Bioaccumulative potential

Does not accumulate in organisms.

Mobility in soil no data available

**PBT and vPvB assessment** no data available

#### Other adverse effects

Biochemical Oxygen 105 mg/g Demand (BOD) Chemical Oxygen 1.894 mg/g Demand (COD)

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

# 13. DISPOSAL CONSIDERATIONS

#### Product

This combustible material may be burned in a chemical incinerator equipped with an afterburner and scrubber. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chemical incinerator equipped with an afterburner and scrubber.

#### **Contaminated packaging**

Dispose of as unused product.

# **14. TRANSPORT INFORMATION**

# DOT (US)

| UN number: 2966 Class: 6.1<br>Proper shipping name: Thioglycol<br>Reportable Quantity (RQ):<br>Marine pollutant: No<br>Poison Inhalation Hazard: No | Packing group: II |                  |  |
|---|-------------------|------------------|--|
| IMDG<br>UN number: 2966 Class: 6.1<br>Proper shipping name: THIOGLYCOL<br>Marine pollutant: No  | Packing group: II | EMS-No: F-A, S-A |  |
| <b>IATA</b><br>UN number: 2966 Class: 6.1<br>Proper shipping name: Thioglycol   | Packing group: II |                  |  |

#### **15. REGULATORY INFORMATION**

#### **OSHA Hazards**

Toxic by inhalation., Toxic by ingestion, Highly toxic by skin absorption, Skin sensitiser, Corrosive, Mutagen

#### SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

|                                       | CAS-No. | Revision Date |
|---------------------------------------|---------|---------------|
| 2-Mercaptoethanol                     | 60-24-2 | 1993-04-24    |
| Pennsylvania Right To Know Components |         |               |
|                                       | CAS-No. | Revision Date |
| 2-Mercaptoethanol                     | 60-24-2 | 1993-04-24    |
| New Jersey Right To Know Components   |         |               |
|                                       | CAS-No. | Revision Date |
| 2-Mercaptoethanol                     | 60-24-2 | 1993-04-24    |
|                                       |         |               |

### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# **16. OTHER INFORMATION**

# **Further information**

Copyright 2012 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.