1

sigma-aldrich.com

**SAFETY DATA SHEET** 

Version 6.1 Revision Date 05/28/2017 Print Date 06/29/2019

# **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Lead oxide
	Product Number Brand Index-No.	:	577847 Aldrich 082-001-00-6
	CAS-No.	:	1314-41-6

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Synthesis of substances

### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich Inc. 3050 Spruce Street ST. LOUIS MO 63103 UNITED STATES	
Telephone	:	+1 314 771-5765	
Fax	:	+1 800 325-5052	
Emergency telephone number			

### 1.4 Emergency telephone number

Emergency Phone # : +1-703-527-3887

# 2. HAZARDS IDENTIFICATION

# 2.1 Classification of the substance or mixture

# GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Oxidizing solids (Category 2), H272 Acute toxicity, Oral (Category 4), H302 Acute toxicity, Inhalation (Category 4), H332 Carcinogenicity (Category 2), H351 Reproductive toxicity (Category 1A), H360 Specific target organ toxicity - repeated exposure (Category 1), H372 Acute aquatic toxicity (Category 1), H400 Chronic aquatic toxicity (Category 1), H410

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

# 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



Hazard statement(s) H272 H302 + H332

May intensify fire; oxidizer. Harmful if swallowed or if inhaled

H351 H360	Suspected of causing cancer. May damage fertility or the unborn child.
H372 H410	Causes damage to organs through prolonged or repeated exposure. Very toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat.
P220	Keep/Store away from clothing/ combustible materials.
P221	Take any precaution to avoid mixing with combustibles.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391	Collect spillage.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

# 3.1 Substances

Synonyms	:	Lead oxide, red Lead(II,IV) oxide Minium
Formula	:	O <sb>4Pb<sb>3</sb></sb>
Molecular weight	:	685.60 g/mol
CAS-No.	:	1314-41-6
EC-No.	:	215-235-6
Index-No.	:	082-001-00-6

# Hazardous components

Component	Classification	Concentration		
<b>Orange lead</b> Included in the Candidate List of Substances of Very High Concern (SVHC) according to Regulation (EC) No. 1907/2006 (REACH)				
	Ox. Sol. 2; Acute Tox. 4; Carc. 2; Repr. 1A; STOT RE 1; Aquatic Acute 1; Aquatic Chronic 1; H272, H302 + H332, H351, H360, H372, H410	<= 100 %		

For the full text of the H-Statements mentioned in this Section, see Section 16.

# **4. FIRST AID MEASURES**

#### 4.1 Description of first aid measures

### General advice

Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

### In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

### In case of eye contact

Flush eyes with water as a precaution.

### If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### 4.3 Indication of any immediate medical attention and special treatment needed No data available

# **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

### Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture 5.2 Lead oxides

#### Advice for firefighters 5.3

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 **Further information**

Use water spray to cool unopened containers.

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid dust formation. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas. Avoid breathing dust. For personal protection see section 8.

#### 6.2 **Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Sweep up and shovel. Contain spillage, and then collect with an electrically protected vacuum cleaner or by wetbrushing and place in container for disposal according to local regulations (see section 13). Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid formation of dust and aerosols. Further processing of solid materials may result in the formation of combu formation should be taken into consideration before additional processing Provide appropriate exhaust ventilation at places where dust is formed.Keep away from sources of ignition - No smoking.Keep away from heat and sources of ignition.

For precautions see section 2.2.

# **Conditions for safe storage, including any incompatibilities** Keep container tightly closed in a dry and well-ventilated place. 7.2

Keep in a dry place.

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 **Control parameters**

# Components with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis			
Orange lead	1314-41-6	TWA	0.050000	USA. ACGIH Threshold Limit Values			
			mg/m3	(TLV)			
	Remarks	Central Nervous System impairment					
		Hematologic effects					
		Peripheral I	Nervous System	impairment			
		Substances for which there is a Biological Exposure Index or Indices					
		(see BEI® s	(see BEI® section)				
		Confirmed animal carcinogen with unknown relevance to humans					
		varies					
		TWA	0.050000	USA. NIOSH Recommended			
			mg/m3	Exposure Limits			
		See Appen	dix C				
		PEL	0.050000	OSHA Specifically Regulated			
			mg/m3	Chemicals/Carcinogens			
		1910.1025					
		If an employee is exposed to lead for more than 8 hou					
		day, the pe	rmissible exposu	re limit, as a time weighted average			
				reduced according to the following			
		formula: Maximum permissible limit (in µg/m3)=400÷hours worked					
		in the day This section applies to all occupational exposure to lead, except a provided in paragraph (a)(2). It does not apply to the construction					
			industry or to agricultural operations covered by 29 CFR part 1928 OSHA specifically regulated carcinogen				
		PEL	0.050000	OSHA Specifically Regulated			
			mg/m3	Chemicals/Carcinogens			
		1910.1025					
		If an employee is exposed to lead for more than 8 hours in any w day, the permissible exposure limit, as a time weighted average					
				reduced according to the following			
			aximum permissik	ble limit (in $\mu$ g/m3)=400÷hours worked			
		in the day					
				cupational exposure to lead, except as			
			provided in paragraph (a)(2). It does not apply to the construction				
				erations covered by 29 CFR part 1928.			
			carcinogen				
		TWA	0.05 mg/m3	USA. ACGIH Threshold Limit Values (TLV)			
			rvous System imp	pairment			
		Hematologic effects					
		Peripheral Nervous System impairment					
				is a Biological Exposure Index or Indices			
		(see BEI® s					
			animal carcinoge	n with unknown relevance to humans			
		varies					

PEL	0.05 mg/m3	OSHA Specifically Regulated Chemicals/Carcinogens
day, the perr (TWA) for the formula: Max in the day This section provided in p industry or to	nissible exposure l at day, shall be rec kimum permissible applies to all occup paragraph (a)(2). It	ad for more than 8 hours in any work imit, as a time weighted average luced according to the following limit (in µg/m3)=400÷hours worked pational exposure to lead, except as does not apply to the construction tions covered by 29 CFR part 1928. rcinogen
TWA	0.05 mg/m3	USA. NIOSH Recommended Exposure Limits
See Appendi	ix C	

# 8.2 Exposure controls

# Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

# Personal protective equipment

### Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

# Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril® (KCL 740 / Aldrich Z677272, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industria situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use (EN 143) respirator cartridges as a backup to engineering controls. If th full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

# Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

		······································	
	a)	Appearance	Form: powder
	b)	Odour	No data available
	c)	Odour Threshold	No data available
	d)	рН	No data available
	e)	Melting point/freezing point	No data available
	f)	Initial boiling point and boiling range	No data available
	g)	Flash point	()Not applicable
	h)	Evaporation rate	No data available
	i)	Flammability (solid, gas)	No data available
	j)	Upper/lower flammability or explosive limits	No data available
	k)	Vapour pressure	No data available
	I)	Vapour density	No data available
	m)	Relative density	No data available
	n)	Water solubility	No data available
	0)	Partition coefficient: n- octanol/water	No data available
	p)	Auto-ignition temperature	No data available
	q)	Decomposition temperature	No data available
	r)	Viscosity	No data available
	s)	Explosive properties	No data available
	t)	Oxidizing properties	The substance or mixture is classified as oxidizing with the
9.2		<b>her safety information</b> data available	

# **10. STABILITY AND REACTIVITY**

#### 10.1 Reactivity No data available

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** No data available
- **10.4 Conditions to avoid** No data available
- **10.5** Incompatible materials Strong reducing agents
- **10.6 Hazardous decomposition products** Hazardous decomposition products formed under fire conditions. - Lead oxides

category 2.

# **11. TOXICOLOGICAL INFORMATION**

# 11.1 Information on toxicological effects

### Acute toxicity

No data availableOrange lead Inhalation: No data available(Orange lead) Dermal: No data available(Orange lead) LD50 Intraperitoneal - Rat - 630 mg/kg(Orange lead)

# Skin corrosion/irritation

No data available(Orange lead)

**Serious eye damage/eye irritation** No data available(Orange lead)

# Respiratory or skin sensitisation

No data available(Orange lead)

### Germ cell mutagenicity

No data available(Orange lead)

# Carcinogenicity

This product is or contains a component that has been reported to be possi classification.(Orange lead) Limited evidence of a carcinogenic effect.(Orange lead)

IARC: 2A - Group 2A: Probably carcinogenic to humans (Orange lead)

2A - Group 2A: Probably carcinogenic to humans (Orange lead)

- NTP: RAHC Reasonably anticipated to be a human carcinogenThe reference note has been added by TD based on the background information of the NTP. (Orange lead)
- OSHA: OSHA specifically regulated carcinogen (Orange lead)

#### **Reproductive toxicity**

Known human reproductive toxicant(Orange lead)

#### **Specific target organ toxicity - single exposure** No data available(Orange lead)

Specific target organ toxicity - repeated exposure No data available

Aspiration hazard No data available(Orange lead)

# **Additional Information**

RTECS: Not available

Lead salts have been reported to cross the placenta and to induce embryo- and feto- mortality. They also have teratogenic effect in some animal species. No teratogenic effects have been reported with exposure to organometallic lead compounds. Adverse effects of lead on human reproduction, embryonic and fetal development, and postnatal (e.g., mental) development have been reported. Excessive exposure can affect blood, nervous, and digestive systems. The synthesis of hemoglobin is inhibited and results in anemia. If left untreated, neuromuscular dysfunction, possible paralysis, and encephalopathy can result. Additional symptoms of overexposure include: joint and muscle pain, weakness of the extensor muscles (frequently the hand and wrist), headache, dizziness, abdominal pain, diarrhea, constipation, nausea, vomiting, blue line on the gums, insomnia, and metallic taste. High body levels produce increased cerebrospinal pressure, brain damage, and stupor leading to coma and often death., Anorexia., Vomiting, Convulsions, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.(Orange lead)

# **12. ECOLOGICAL INFORMATION**

#### 12.1 Toxicity No data available

- **12.2 Persistence and degradability** No data available
- **12.3 Bioaccumulative potential** No data available

12.4 Mobility in soil No data available(Orange lead)

12.5 Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Very toxic to aquatic life with long lasting effects.

# **13. DISPOSAL CONSIDERATIONS**

### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber b highly flammable. Offer surplus and nonrecyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Dissolve or mix the material with a combustible solvent and burn in a chem scrubber.

# Contaminated packaging

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 1479 Class: 5.1 Packing group: II Proper shipping name: Oxidizing solid, n.o.s. (Orange lead) Poison Inhalation Hazard: No

# IMDG

UN number: 1479 Class: 5.1 Packing group: II Proper shipping name: OXIDIZING SOLID, N.O.S. (Orange lead) Marine pollutant : yes EMS-No: F-A, S-Q

# ΙΑΤΑ

UN number: 1479 Class: 5.1 Packing group: II Proper shipping name: Oxidizing solid, n.o.s. (Orange lead)

# **15. REGULATORY INFORMATION**

# SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# SARA 311/312 Hazards

Reactivity Hazard, Acute Health Hazard, Chronic Health Hazard

# Massachusetts Right To Know Components

	CAS-No.	Revision Date
Orange lead	1314-41-6	1993-04-24
Pennsylvania Right To Know Components		
	CAS-No.	Revision Date
Orange lead	1314-41-6	1993-04-24
New Jersey Right To Know Components		
	CAS-No.	Revision Date
Orange lead	1314-41-6	1993-04-24
California Prop. 65 Components		
WARNING! This product contains a chemical known to the	CAS-No.	Revision Date
State of California to cause cancer. Orange lead	1314-41-6	2007-09-28

# **16. OTHER INFORMATION**

### Full text of H-Statements referred to under sections 2 and 3.

H272	May intensify fire; oxidizer.
H302	Harmful if swallowed.
H302 + H332	Harmful if swallowed or if inhaled
H332	Harmful if inhaled.
H351	Suspected of causing cancer.
H360	May damage fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

#### **HMIS** Rating

Health hazard:	2
Chronic Health Hazard:	*
Flammability:	0
Physical Hazard	2
NFPA Rating	
Health bazard	2

Health hazard:	2
Fire Hazard:	0
Reactivity Hazard:	2
Special hazard.I:	ОХ
1	

#### **Further information**

Copyright 2016 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

# **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956 Version: 6.1 Re

Revision Date: 05/28/2017

Print Date: 06/29/2019